

GTP Series Power Distribution Boxes

(248) 356-2839


Compact grounded power distribution with removable insulated mounting feet for transgun applications

FEATURES

- Utilizes Compact Series Power Distribution Blocks
- ANSI 61 Gray standard color
- Ground terminal is bonded to the enclosure for safety
- Removable insulating feet to isolate robot from ground currents
- Conductor size range 300 MCM- 6 AWG
- Choice of conductor and ground terminals
- 'DANGER 480/575 VOLTS' labeling
- 'Value Added' services available
 cord grips/ strain reliefs added, transgun cables, robotic dressout assistance, etc.



DIMENSIONS



E	nclosure	Dimensions - in [mm]									
	Type		Overall	Mounting							
		Α	В	С	D	E					
1	12 x 6 x 4	4.28	6.00	12.00	4.00	12.75					
'	12 X 0 X 4	[108.7]	[152.4]	[304.8]	[101.6]	[323.9]					
2	12 x 6 x 6	6.28	6.00	12.00	4.00	12.75					
	12 X 0 X 0	[159.5]	[152.4]	[304.8]	[101.6]	[323.9]					
3	10 x 10 x 4	4.28	10.00	10.00	8.00	10.75					
'	10 × 10 × 4	[108.7]	[254.0]	[254.0]	[203.2]	[273.1]					

Removable insulating feet.

PART NUMBER SHOWN - GTP-SN12-ST3-1B

Notice: The information contained herein is, to the best of our knowledge, true, accurate and reliable. Since procedures and conditions under which these products may be used are beyond our control, no warranty, expressed or implied, is made to their performance.



Syndevco Inc. Sheet: 141114



GTP Series Power Distribution Boxes

PART NUMBERING

GENERIC PART NUMBER: GTP-AAAB-CCC-DE-F SAMPLE PART NUMBER: GTP-SN12-ST3-1B


GTP-

- [AAA						В ССС					D		E		F	
		CONDUCTOR NUMBER OF						GROUND				ENCLOSURE		ENCLOSURE		ADDITIONAL	
		TYPE CONDUCTO				DUCTOR	TYPE				SIZE		COLOR		OPTIONS		
			LINE	LOAD POLES		POLES		LINE		LOAD							
		QTY WIRE RANGE QTY WIRE RANG					QTY WIRE RANGE QTY WI		TY WIRE RANGE								
	AM3	1	300MCM-	1 30	300MCM-	4	ONE	SM3	1	300MCM-	2	1/OAWG-		12x6x4	В	ANSI61 Gray/	Leave blank for
'	AIVIS	'	1/O AWG		1/O AWG	'			1 1	1/O AWG		6 AWG	1	Mounting Feet		GR/GR	none or see a
	CNA	1	300MCM-	2	1/OAWG-	2	TWO	CTO	2	1/OAWG-	2	1/OAWG-		Opposite of hinge			Syndevco
1	SM3	۱ '	1/O AWG		6 AWG	~	1000	ST3) ²	6 AWG		6 AWG		12x6x6			Representative
Ι.	0.70	٥	1/OAWG-	2	1/OAWG-		TIDEE	•	· · · · · · · · · · · · · · · · · · ·			2	Mounting Feet				
	ST3	2	6 AWG		6 AWG	3	3 THREE							Opposite of hinge			
-	CNIA	4	1/O AWG-	4	1/O AWG-									10x10x4	See a Syndevco		
;	SN1	1	6 AWG	1	6 AWG	See a							3	Mounting Feet	Representative for		
Ī	See a Syndevco Representative for further options See a Syndevco Representative for further options						See a Syndevco Representative for further options					Opposite of hinge	fı	urther options			
								iditilei options									
												See a Syndevco					
							options						Representative for				
														further options			

Please see our Strain Relief products for further design solutions



3000 Series Strain Aids



2490 Series Split Bushings





7000 Series Cage Bushings

Notice: The information contained herein is, to the best of our knowledge, true, accurate and reliable. Since procedures and conditions under which these products may be used are beyond our control, no warranty, expressed or implied, is made to their performance.



Syndevco Inc.